

07330-1
 07330-2
 07330-3
 07330-4
 07330-5
 07330-6
 07330-7
 07330-8
 07330-9
 07330-10
 07330-11
 07330-12
 07330-13
 07330-14
 07330-15
 07330-16
 07330-17
 07330-18
 07330-19
 07330-20
 07330-21
 07330-22
 07330-23
 07330-24
 07330-25
 07330-26
 07330-27
 07330-28
 07330-29
 07330-30
 07330-31
 07330-32
 07330-33
 07330-34
 07330-35
 07330-36
 07330-37
 07330-38
 07330-39
 07330-40
 07330-41
 07330-42
 07330-43
 07330-44
 07330-45
 07330-46
 07330-47
 07330-48
 07330-49
 07330-50
 07330-51
 07330-52
 07330-53
 07330-54
 07330-55
 07330-56
 07330-57
 07330-58
 07330-59
 07330-60
 07330-61
 07330-62
 07330-63
 07330-64
 07330-65
 07330-66
 07330-67
 07330-68
 07330-69
 07330-70
 07330-71
 07330-72
 07330-73
 07330-74
 07330-75
 07330-76
 07330-77
 07330-78
 07330-79
 07330-80
 07330-81
 07330-82
 07330-83
 07330-84
 07330-85
 07330-86
 07330-87
 07330-88
 07330-89
 07330-90
 07330-91
 07330-92
 07330-93
 07330-94
 07330-95
 07330-96
 07330-97
 07330-98
 07330-99
 07330-100
 07330-101
 07330-102
 07330-103
 07330-104
 07330-105
 07330-106
 07330-107
 07330-108
 07330-109
 07330-110
 07330-111
 07330-112
 07330-113
 07330-114
 07330-115
 07330-116
 07330-117
 07330-118
 07330-119
 07330-120
 07330-121
 07330-122
 07330-123
 07330-124
 07330-125
 07330-126
 07330-127
 07330-128
 07330-129
 07330-130
 07330-131
 07330-132
 07330-133
 07330-134
 07330-135
 07330-136
 07330-137
 07330-138
 07330-139
 07330-140
 07330-141
 07330-142
 07330-143
 07330-144
 07330-145
 07330-146
 07330-147
 07330-148
 07330-149
 07330-150
 07330-151
 07330-152
 07330-153
 07330-154
 07330-155
 07330-156
 07330-157
 07330-158
 07330-159
 07330-160
 07330-161
 07330-162
 07330-163
 07330-164
 07330-165
 07330-166
 07330-167
 07330-168
 07330-169
 07330-170
 07330-171
 07330-172
 07330-173
 07330-174
 07330-175
 07330-176
 07330-177
 07330-178
 07330-179
 07330-180
 07330-181
 07330-182
 07330-183
 07330-184
 07330-185
 07330-186
 07330-187
 07330-188
 07330-189
 07330-190
 07330-191
 07330-192
 07330-193
 07330-194
 07330-195
 07330-196
 07330-197
 07330-198
 07330-199
 07330-200
 07330-201
 07330-202
 07330-203
 07330-204
 07330-205
 07330-206
 07330-207
 07330-208
 07330-209
 07330-210
 07330-211
 07330-212
 07330-213
 07330-214
 07330-215
 07330-216
 07330-217
 07330-218
 07330-219
 07330-220
 07330-221
 07330-222
 07330-223
 07330-224
 07330-225
 07330-226
 07330-227
 07330-228
 07330-229
 07330-230
 07330-231
 07330-232
 07330-233
 07330-234
 07330-235
 07330-236
 07330-237
 07330-238
 07330-239
 07330-240
 07330-241
 07330-242
 07330-243
 07330-244
 07330-245
 07330-246
 07330-247
 07330-248
 07330-249
 07330-250
 07330-251
 07330-252
 07330-253
 07330-254
 07330-255
 07330-256
 07330-257
 07330-258
 07330-259
 07330-260
 07330-261
 07330-262
 07330-263
 07330-264
 07330-265
 07330-266
 07330-267
 07330-268
 07330-269
 07330-270
 07330-271
 07330-272
 07330-273
 07330-274
 07330-275
 07330-276
 07330-277
 07330-278
 07330-279
 07330-280
 07330-281
 07330-282
 07330-283
 07330-284
 07330-285
 07330-286
 07330-287
 07330-288
 07330-289
 07330-290
 07330-291
 07330-292
 07330-293
 07330-294
 07330-295
 07330-296
 07330-297
 07330-298
 07330-299
 07330-300

BACKGROUND OF THE INVENTION

[0002] The present invention relates to a portable-type information apparatus such as a notebook-type personal computer or a word processor, particularly to a portable-type information apparatus which is largely improved in extendability and portability.

[0003] Recently, miniaturization of portable-type information apparatuses such as notebook-type personal computers has been significantly accelerated due to the rapid progress of electronic technology, whereby the user can always carry the information apparatus with him even outside the office.

[0004] Information apparatuses, particularly notebook type personal computers, have often been provided with various connectors for the connection of external keyboards, mice, external CRTs, printers or others, for extending the functions thereof.

[0005] Since recently marketed notebook-type personal computers have already been miniaturized in size and weight to a large extent, it is difficult to further improve the portability without sacrificing the extendability.

[0006] Accordingly, an object of the present invention is to provide a reasonable and economical information apparatus of a portable type improved in operability and portability without deteriorating the extendability, based on a novel technical idea.

SUMMARY OF THE INVENTION

[0007] According to one aspect of the present invention, a portable-type information apparatus having an information apparatus body comprises a detachable connector unit provided with a plurality of connectors adapted to be detachably connected to peripheral units and with at least one connector adapted to be detachably connected to the information apparatus body; connection means provided on the information apparatus body, for the connection between the connector unit and the information apparatus body; and a detachable battery unit containing at least one battery and having substantially the same size as that of the connector unit; and wherein the battery unit and the connector unit can alternatively be connected to the information apparatus in substantially the same connecting position relative to the information apparatus body.

[0008] Preferably the battery unit is connected to the information apparatus body through the connection means. Also, preferably, coupling means are provided to transmit electrical power from the battery unit to the information apparatus body. Preferably, at least one fastener unit is mounted between the information apparatus body and the connector unit affording mechanical detachable fixation therebetween. Also, preferably, the connector unit is mechanically detachably fixed to the information apparatus body through said at least one fastener unit. Preferably, the connector unit and the battery unit are alternatively detachably fixed to the back side of the information apparatus body.

[0009] According to another aspect of the present invention, a portable-type information apparatus having an information apparatus body comprises a detachable connector unit provided with a plurality of connectors adapted to be detachably connected to peripheral units and with at least one connector adapted to be detachably connected to the information apparatus body connection means provided on the information apparatus body, for the connection between the connector unit and the information apparatus body; and a detachable battery unit containing at least one battery and having substantially the same size as that of the connector unit, said battery unit being connectable to the information apparatus body through the connection means.

Swat
a1 [0010] Preferably, coupling means is provided to transmit electrical power from the battery unit to the information apparatus body. Also, preferably, at least one fastener unit is mounted between the information apparatus body and the connector unit for a mechanical detachable

fixation therebetween. Preferably, the connector unit is mechanically detachably fixed to the information apparatus body through said at least one fastener. Also, preferably, the connector unit and the battery unit are alternatively detachably fixed to the back side of the information apparatus body.

[0011] According to further aspect of the invention, a connector unit adapted to be detachably connected to a portable-type information apparatus having an information apparatus body comprises a plurality of connectors adapted to be detachably connected to peripheral units; at least one connector adapted to be detachably connected to the information apparatus body; and at least one battery enclosed therein to supply electrical power to the information apparatus body.

[0012] Preferably, connection means are provided for the connection between the connector unit and the information apparatus body and wherein coupling means is provided to supply electrical power from said at least one battery to the information apparatus. Also, preferably, at least one fastener unit is provided between the information apparatus body and the connector unit for a mechanical detachable fixation therebetween. Preferably, it is detachably fixed to the back side of the information apparatus body.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] These and other objects of the present invention will become apparent from the following detailed description of the preferred embodiment of the invention, taken in connection with the accompanying drawings.

[0014] In the drawings:

Fig. 1 is a plan view of a notebook type personal computer according to one embodiment of the present invention, in an open state;

Fig. 2A is a perspective view as seen from a front side, and Fig. 2B is a perspective view as seen from a rear side, of the comparator of Fig. 1, illustrating the relationship of a connector box relative to the personal computer;

Fig. 3A is a rear view, Fig. 3B is a top view, Fig. 3C is a front view and Fig. 3D is a leftside view, of the connector box;

Fig. 4 is an enlarged side sectional view of a main part of a fastener;

Fig. 5 is a plan view of a connector box accommodating batteries therein;
Fig. 6 is a plan view of a battery pack.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] The present invention will be described in more detail below with reference to the preferred embodiments illustrated in the attached drawings.

[0016] Fig. 1 is a schematic plan view of a notebook-type personal computer 1 according to one embodiment of the present invention. With reference to this drawing, the personal computer 1 consists of a lower housing 5 which is built in a main circuit board carrying a CPU or other components, and having a keyboard 3 on the upper surface thereof, and an upper housing 9 coupled, in a hinged manner, to an edge portion (innermost side) of the lower housing 5 and having a liquid crystal display 7 in a central area thereof. The upper housing 9 is folded onto the lower housing 5 to form an integral case convenient for transportation.

[0017] On the operator's side relative to the keyboard 3 extending in the central area of the upper surface of the lower housing 5, there is provided a palm rest section 11 wherein a pointing device 13 of a ball type is provided at a center thereof.

[0018] A hinge section 15 is provided along the innermost edge of the lower housing 5, farthest from the operator's side beyond the keyboard 3, for coupling to the upper housing 9 while leaving an upper surface vacant space 17 of about 20 mm wide between the hinge section 15 and the keyboard 3.

[0019] In a central region of the upper surface vacant area 17, a suspend/resume key 21 is provided. The suspend/resume key 21 has a function of interrupting the supply of electric power to electronic parts, including CPU and those relating to the output/input, except for memories, so that the power consumption in the personal computer is restricted (i.e., limited) to a lower level than a normal operating power consumption level.

[0020] The liquid crystal display 7, of a rectangular shape and large size is provided in a central area of the display surface of the upper housing 9. Generally in a lower area of the upper housing beneath the liquid crystal display 7, a so-called state-displaying section 31 is provided in a central region which confronts the suspend/resume key 21 of the lower housing 5 when the upper housing 9 is closed (folded) to the lower housing 5. A sound output section 33 having a

number of small apertures is provided on both sides of the state-displaying section 31.

[0021] The state-displaying section 31 has a function of visually displaying whether or not a predetermined electronic device, internal or external to the personal computer is operative or inoperative, and basically consists of an elongated liquid crystal substrate 35.

[0023] As shown in Figs. 2A and 2B, the common connector 51 on the rear surface of the lower housing 5 (of the personal computer 1) is adapted to be detachably connected to a connector section 55 provided on a rectangular front surface of a connector box 53 (which is also called a port replicator) so that the connector box 53 is detachably mounted to the rear surface of the lower housing 5.

[0025] The connector section 55 on the front surface of the connector box 53 consists of a terminal having 60 pins and a pair of guide pins 57 on both sides thereof for facilitating the connector engagement. The guide pins 57 are engageable with corresponding guide holes (not shown) provided at corresponding positions in the lower housing and also function as grounding connectors.

[0027] As shown in Fig. 4, the fastener 61 basically consists of a threaded rod 63 so as having a thread at a tip 30 end, a main body 65 accommodating the threaded rod 63 so as to be movable in the axial direction and coupled to the threaded rod 63 to be rotatable therewith, and a compression coil spring 67 mounted within the main body 65 for biasing the threaded rod 63

choice.

[0039] While the above-mentioned embodiments are limited to the application of the present invention to a personal computer, the present invention should not be limited thereto but may be effectively applicable also to other portable-type electronic apparatuses such as a word processor.

[0041] Also, the connector box according to the present invention is easily handled and can be mounted to the portable type information apparatus in a simple manner, resulting in an improvement in extendability of the portable-type information apparatus and a reduction in the weight thereof. If a fastener is provided, the connector box can be rigidly fixed to result in favorable stability and mechanical strength. If a battery is provided, it is possible to prolong the operating time without deteriorating the extendability.

[0043] It is to be understood that the invention is by no means limited to the specific embodiments illustrated and described herein, and that various modifications thereof may be made which come within the scope of the present invention as defined in the appended claims.